



KEY FEATURES

- High Quality high definition two way In-ceiling speaker for Hi-Fi, Home theater and all background music applications
- High Power handling
- High Quality black kevlar cone with 1" ferrofluid cooled silk dome tweeter with swivel mount for high end sound quality
- Magnetic Grille and dog ears for effortless ceiling mounting
- Complete flush mount, no bezel visible only metallic grille visible
- All high end components used for superior sound quality

APPLICATIONS

The iComm CS6.2 Loudspeaker is a 6.5" Two way Ceiling speaker suitable for

- Restaurants, Offices, Auditoriums, Gymnasiums, Home theater, Conference rooms, AV rooms etc
- Contractors, Custom Installers & Retailers

SPECIFICATIONS

Power Handling	: 50W RMS / 100W Program / 200W Peak
Nominal Impedance	: 8 ohms
Frequency Response	: 45Hz – 20KHz
Average Sensitivity	: 89dB/W/m
Calculated Max SPL	: 106dB Continuous 109dB Program 112dB Peak
LF	: 6.5" Black Kevlar cone woofer
HF	: 1" Ferro fluid cooled silk dome
Connectors	: Spring Push Loaded
Cabinet	: ABS with Magnetic Grille
Size (WxD)	: 250x98mm
Cutout Size	: 209mm
Mounting Depth	: 95mm
Net weight	: 1.5Kg