



KEY FEATURES

- High quality, high definition two way monitor speaker for indoor / outdoor applications
- 5" Polypropylene LF driver with rubber surround & 1" silk dome tweeter.
- Rear mounted passive radiator for extended low frequency response, can be used without subwoofer also
- Easy mounting bracket included
- High quality ABS cabinet with rust proof grille
- Complete weather proof outdoor capable

APPLICATIONS

The iComm Monitor is a multipurpose monitor speaker suitable for

- Indoor Applications: Restaurants, Offices, Museums, Home theater, Auditoriums, Gymnasiums and more
- Outdoor Applications: Atriums, Pool Side, Sun Rooms, Patios, Backyards and more
- Contractors, Custom Installers & Retailers

SPECIFICATIONS

Power Handling	: 50W RMS / 100W Program / 200W Peak
Nominal Impedance	: 8 ohms
Frequency Response	: 70Hz – 20KHz
Average Sensitivity	: 85dB/W/m
Calculated Max SPL	: 101dB Continuous 104dB Program 107dB Peak
LF	: 5" PP woofer with rear mounted passive radiator
HF	: 1" Silk dome tweeter
Connectors	: Phoenix
Cabinet	: ABS
Outdoor Capable	: Yes
Size (WxHxD)	: 185x305x200mm
Net weight	: 3Kg