



KEY FEATURES

- The highest SPL of the category
- Real 1000W RMS power capacity
- Top of the Line performance and reliability
- Highly dynamic and holographic reproduction
- Premium custom made Neodymium European drivers
- Aquaplasted TC4 Diaphragm for ultra smooth HF reproduction
- Proprietary 60° x 40° constant directivity rotatable horn
- Touring grade textured black paint finish

SPECIFICATIONS

Power Handling	1600W RMS (AES) 3200W Program / 6400W Peak
Nominal impedance	4 ohms
Frequency response -6dB half space	45Hz - 18000Hz
Average Sensitivity	100dB/W/m
Calculated Maximum SPL / 1m	132dB continuous 135dB Program 138dB Peak
Nominal Directivity	60° x 40° asymmetric (10° up, 30° down) above 1000Hz
Recommended low cut filter	30Hz 24dB/oct in full range mode 60-100Hz with subwoofer
Low Frequency driver	Custom made 15" CELTO Acoustique Neodymium magnet, 4" Voice coil
High Frequency driver	1.4" exit CELTO Acoustique Ferrite magnet, 3" Aquaplasted TC4 diaphragm
Crossover	Passive mode only 1400Hz, 12dB/oct on LF, 18dB/oct on HF
Flying hardware	10 M8 points
Connectors	2pcs NEUTRIK Speakon® NL4MP (1+/- Input)
Floor Monitor use	No
Pole mount	No
Cabinet	CNC made with tongue and groove assembly 18mm birch plywood
Finish	Touring grade textured black coating
Size (WxHxD)	465x1170x478mm 18.3"x46.0"x18.8"
Weight	52Kg (114.6lbs)

APPLICATIONS

The ZX152 Loudspeaker is suitable for near field main PA reinforcement with or without subwoofer, portable or permanent installation, monitor in stages, and delay fill. Suitable in spaces like

- FoH
- Multi-functional room
- Auditorium and Theatre
- Pub
- Bar
- Night club
- Commercial announcements
- Touring and rental applications