



KEY FEATURES

- Real 1800W RMS power capacity
- Premium 21" LF driver with massive $\pm 16\text{mm}$ linear Xmax
- Triple forced cooling system for low power compression
- Heavy braced cabinet for vibration free dynamic response
- Rear loaded transmission line loading for fast response
- Touring grade textured black paint finish

SPECIFICATIONS

Power Handling	1800W RMS (AES) 3600W Program / 7200W Peak
Nominal impedance	4 ohms
Frequency response -6dB half space	28Hz - 800Hz
Average Sensitivity	104dB/W/m
Calculated Maximum SPL / 1m	136dB continuous 139dB Program 142dB Peak
Recommended filter	High-pass: 30Hz 24dB/oct Low-pass: 80-110Hz
Nominal Directivity	Omni in useable band
Low Frequency driver	Custom made 21" CELTO Acoustique 5" In / Out Voice coil
Crossover	No, only active mode
Flying hardware	No, stack ground use only
Connectors	2pcs NEUTRIK Speakon® NL4MP (1+/1- Input)
Pole mount	Yes, 35mm
Cabinet	CNC made with tongue and groove assembly 25mm birch plywood
Finish	Touring grade textured black coating
Size (WxHxD)	850x580x750mm 33.5"x22.8"x29.5"
Weight	67Kg (147.7lbs)

APPLICATIONS

The SW121s subwoofer is suitable for bass reinforcement for main PA systems, touring or permanent installations for small to large stages, indoor or outdoor live performances. Suitable in spaces like:

- FoH
- Multi-functional room
- Auditorium and Theatre
- Pub
- Bar
- Night club
- Commercial announcements