
QX8HP High Performance Series





The discreet design with reticulated foam front and textured black paint finish and multiple integrated fixing points achieves a high class look suitable for any application.

Designed with a VAL audio 8" custom 200 W, 8 Ohm woofer and 1.4" compression driver, the internal passive crossover ensures a linear, usable frequency response of 62 Hz to 20 kHz (-6 dB) across an asymmetric H50° to 100° x V55° dispersion with rotatable CD horn. A maximum SPL of 125 dB (peak). Sharing voicing characteristics with the rest of the QX series allowing them to be used simultaneously, keeping a consistent tone.

Mounting options include integrated 12 x M8 fixing points along with the Vertical Yoke.

The rear cast aluminum connection plate has two 4 pin speakON® connectors fitted as standard, one input and one link. The speakon connectors are wired on pins +1-1, with pass through of pins +2-2.



Die Liebe zur Musik



KEY FEATURES

- High Power 200W RMS power capacity
- Extremely smooth sounding fullrange loudspeaker
- High quality custom premium European
- Proprietary asymmetric rotatable CD Horn
- HF High power 1" exit compression driver with 1.4" diaphragm
- Multi purpose cabinet design for FOH or monitor use
- Birch plywood cabinet
- Touring grade textured waterborne black, scratch resistant coating
- Tropicalized moisture free construction (hardware and drivers)
- Comprehensive flying hardware M8 inserts



TECHNICAL SPECIFICATIONS

Design

8" Reflex Tuned, Mid High Point Source Cabinet

Impedance

8 Ohm

Power Handling (AES)

200 Watts (continuous)

Max. Power Handling (AES)

400 Watts (program) 800 Watts (peak)

Sensitivity 1W / 1m

96 dB

Max. SPL

119 dB cont 125 dB peak

∪sable Frequency Range (-6 dB)

62 Hz - 20 kHz

Dispersion

50° to 100° x 55°, Rotational

SYSTEM OPERATION

Recommended Amplification

200 - 400 Watts

System Controller

optional

Speaker Cables

Min - 2 x 2.5 mm2

Preferred - 2 x 4 mm2

PRODUCT FEATURES

Components

1 x 8" Low Frequency Driver 1 x 1.4" Horn loaded Compression Driver

Crossover

Passive - 1.7kHz

Connectors

1 x 4 pole Speakon Connectors

Dimensions (H x W x D mm)

417 x 266 x 234

Weight (kg)

10

Shipping Weight (kg)

11.5 (1 cabinet per carton)

Colour

Black

Rigging

12 x M8 mounting points for horizontal and vertical flying, Vertical U bracket included

Additional Descriptive Data

Birch plywood construction, with durable touring grade scratch resistant black textured paint finish, kick-proof steel grill and black foam with VAL audio logo.

MEASUREMENT



