iComm CS5.2T Two way Ceiling Speaker





KEY FEATURES

- High quality compact two way coaxial ceiling speaker
- High power handling 30W RMS
- 5.25" Polypropylene woofer with rubber surround for extended low frequency response
- 0.75" Polycarbonate tweeter with swivel mount for high frequency directivity
- Dog ears for effortless ceiling mounting
- All high end components used for superior sound quality
- High performance 100V LMT inbuilt -15W and 10W selectable via switch
- Ivory White colour

APPLICATIONS

The iComm CS5.2T loudspeaker is a 5.25" two way coaxial ceiling speaker suitable for

- Restaurants, offices, auditoriums, gymnasiums, conference rooms, AV rooms, BGM applications
- Music, Hi-Fi and home theater applications
- Contractors, custom installers & retail stores

iComm CS5.2T Two way Ceiling Speaker





SPECIFICATIONS	
Driver Power Handling	30W RMS / 60W Program / 120W Peak
Nominal Impedance	8 ohms
Frequency Response (-10dB)	58Hz – 20KHz
Average Sensitivity	89dB/W/m
Calculated Max SPL	104dB Continuous / 107dB Program / 110dB Peak
Low Frequency Driver	5.25" Polypropylene woofer with rubber surround
High Frequency Driver	0.75" Polycarbonate swivel tweeter
Input Connectors	Spring loaded push type terminals
LMT	15W & 10W tapping via switch
Cabinet	ABS with high quality metal grille
Colour	Ivory white
Dimensions (Dia. x Depth)	200 x 68mm
Cutout Size	172mm
Net weight	1.05Kg