iComm CS6.2 High Performance Ceiling Speaker





KEY FEATURES

- High quality high definition two way coaxial ceiling speaker
- High power handling featuring high performance crossover
- High quality black kevlar cone
- Ferrofluid cooled silk dome tweeter with swivel mount for high frequency directivity
- Magnetic grille and dog ears for effortless ceiling mounting
- Architects delight complete flush mount, no bezel visible only metallic grille visible
- All high end and audiophile grade components used for superior sound quality
- LMT version available
- Pearl White colour

APPLICATIONS

The iComm CS6.2 loudspeaker is a 6.5" two way coaxial ceiling speaker suitable for

- Restaurants, offices, auditoriums, gymnasiums, conference rooms, AV rooms, BGM applications
- Music, Hi-Fi and home theater applications
- Contractors, custom installers & retail stores

iComm CS6.2 High Performance Ceiling Speaker





SPECIFICATIONS	
Power Handling (AES Standard)	50W RMS / 100W Program / 200W Peak
Nominal Impedance	8 ohms
Frequency Response (-10dB)	50Hz – 20KHz
Average Sensitivity	89dB/W/m
Calculated Max SPL	106dB Continuous / 109dB Program / 112dB Peak
Low Frequency Driver	6.5" Kevlar cone woofer with rubber surround
High Frequency Driver	1" Ferrofluid cooled silk dome
Input Connectors	Spring push loaded
LMT	Optional extra
Cabinet	ABS with magnetic grille
Size (WxHxD)	250 x 98mm
Cutout Size	209mm
Mounting Depth	95mm
Net weight	1.75Kg