iComm PA6T Wall Mount PA Speaker





KEY FEATURES

- High quality, high definition full range wall mount speaker for PA applications
- Power handling 15W RMS
- 6" Full range driver for clean sound reproduction
- Only 100V operation possible. 100V LMT inbuilt with 15W, 7.5W and 3.75W
 tapping
- Suitable for speech and music applications
- Innovative and unobtrusive slim profile with curved front design
- Easy mounting key holes on the rear
- High quality ABS cabinet
- Spring loaded push type terminals for easy connectivity
- Ivory White colour

APPLICATIONS

The iComm PA6T is a PA full range multipurpose wall mounting speaker suitable for

- Department stores
- Schools
- Offices
- Stadium
- Metro Station
- BPOs

iComm PA6T Wall Mount PA Speaker







SPECIFICATIONS	
Power Handling (AES Standard)	15W RMS / 30W Program / 60W Peak
Rated Impedance	833 Ω / 1667 Ω / 3333 Ω
Frequency Response (-10db)	110Hz – 13kHz
SPL at 1W (at 1kHz,1M)	92dB Continuous / 95dB Program / 98dB Peak
Dispersion Angle	170°
Driver	6" full range driver
Input Connectors	Spring loaded push type terminals
LMT	15W, 7.5W and 3.75W tapping
Cabinet	ABS with wire mesh metal grille
Colour	Ivory white
Size (WxHxD)	243 x 345 x 100mm
Net weight	1.50Kg