iComm WM52T-BLK

Indoor / Outdoor High Performance Wall Mount Speaker





KEY FEATURES

- High quality, high definition two way monitor speaker for indoor / outdoor applications
- Audiophile grade components used
- 5" Polypropylene LF driver with rubber surround
- 1" Silk dome tweeter for smooth HF response
- Rear mounted passive radiator provides extended low Frequency response, can be used without subwoofer
- In-built LMT for 100V/8 ohm operation, multiple tapping
- Innovative design with easy mounting bracket included
- High quality weatherised ABS cabinet designed to meet IP55 standard
- Complete whether proof outdoor capable with rust proof grille
- Phoenix terminals for easy connectivity
- Black colour

APPLICATIONS

The iComm WM52T is two way multipurpose monitor speaker suitable for

- Indoor applications: Restaurants, offices, museums, home theater, auditoriums, gymnasiums, F&B establishments
- Outdoor applications: Atriums, pool side, patios, backyards and more
- Contractors, custom installers & retail stores

iComm WM52T-BLK Indoor / Outdoor High Performance

Wall Mount Speaker







SPECIFICATIONS	
Power Handling (AES Standard)	50W RMS / 100W Program / 200W Peak
Nominal Impedance	8 ohms
Frequency Response (-6db Half space)	70Hz – 20KHz
Average Sensitivity	85dB/W/m
Calculated Max SPL	101dB Continuous / 104dB Program / 107dBPeak
Low Frequency Driver	5" Polypropylene cone woofer with rubber surround and rear mounted passive radiator
High Frequency Driver	1" silk dome tweeter
Input Connectors	Phoenix terminals
100V/70V Connectivity	Yes, multiple tapping via switch
Cabinet	High Quality, impact resistance ABS with rust proof aluminum grille
Wall mount bracket	Included, heavy duty U bracket with multiple installation points
Outdoor Capable	Weatherised to meet IP55 standard
Size (WxHxD)	185 x 305 x 200mm
Net weight	3.10Kg