iComm SMS62T

Indoor / Outdoor Surface Mount Speaker





KEY FEATURES

- High quality two way surface mount speaker for indoor / outdoor applications
- High power handling 60W RMS
- 6.5" Polypropylene LF driver with rubber surround
- 1" Silk dome tweeter for smooth HF response
- In-built LMT for 100V/8 ohm operation, multiple tapping
- Innovative design with easy mounting adjustable swivel bracket for horizontal and vertical mounting on wall / ceiling
- High quality weatherised ABS cabinet with rust proof grille for outdoor usage
- Complete weather proof outdoor capable designed to meet IP55 standards
- Rear protective cover to prevent water ingress
- Available in Black colour


APPLICATIONS

The iComm SMS62T is two way multipurpose monitor speaker suitable for

- Indoor applications: Restaurants, offices, museums, home theater, auditoriums, gymnasiums, F&B establishments
- Outdoor applications: Atriums, pool side, patios, backyards and more
- Contractors, custom installers & retail stores

iComm SMS62T Indoor / Outdoor Surface Mount Speaker







SPECIFICATIONS	
Power Handling (AES Standard)	60W RMS / 120W Program / 240W Peak
Nominal Impedance	8 ohms
Frequency Response (-10dB)	65Hz – 20KHz
Average Sensitivity	89dB/W/m
Calculated Max SPL	108dB Continuous / 111dB Program / 114dB Peak
Low Frequency Driver	6.5" Polypropylene woofer with rubber surround
High Frequency Driver	1" tweeter
Input Connectors	Binding post push terminals
100V Connectivity	6W, 12W, 25W & 50W selectable via rotary switch
Cabinet	High quality, ABS with rust proof aluminum grille
Colour	Black
Wall mount bracket	Included, heavy duty swivel U bracket for horizontal and vertical mounting
Outdoor Capable	Weatherized designed to meet IP55 standards
Size (WxHxD)	196 x 302 x 193mm
Net weight	3.5Kg