iComm CS4.2T Two way Ceiling Speaker





KEY FEATURES

- High quality compact two way coaxial ceiling speaker
- High power handling 25W RMS
- 4" Polypropylene woofer with rubber surround for smooth response
- ½" Polymer tweeter for high frequency reproduction
- Dog ears for effortless ceiling mount
- All high end components used for superior sound quality
- High performance 100V LMT inbuilt with 5W and 2.5W tapping
- Pearl White colour

APPLICATIONS

The iComm CS4.2T loudspeaker is a 4" two way coaxial ceiling speaker suitable for

- Restaurants, offices, auditoriums, gymnasiums, conference rooms, AV rooms, BGM applications
- Music, Hi-Fi and home theater applications
- Contractors, custom installers & retail stores

iComm CS4.2T Two way Ceiling Speaker





SPECIFICATIONS	
Driver Power Handling	25W RMS / 50W Program / 100W Peak
Frequency Response (-10dB)	88Hz – 20KHz
Average Sensitivity	88dB/W/m
Calculated Max SPL	102dB Continuous / 105dB Program / 108dB Peak
Low Frequency Driver	4" Polypropylene woofer with rubber surround
High Frequency Driver	½" Polymer tweeter
Input Connectors	Wire connection
LMT	Yes, 5W and 2.5W tapping
Cabinet	ABS with wire mesh metal grille
Size	175 x 65mm
Ceiling Cutout Size	140mm
Mounting Depth	65mm
Net weight	0.850Kg