# iComm SMS52T

Indoor / Outdoor Surface Mount Speaker





### **KEY FEATURES**

- High quality two way surface mount speaker for indoor / outdoor applications
- Only high quality components used
- 5.25" Polypropylene LF driver with rubber surround
- 0.5" Mylar tweeter for smooth HF response
- In-built LMT for 100V/8 ohm operation, multiple tapping
- Innovative design with easy mounting adjustable swivel bracket for horizontal and vertical mounting on wall / ceiling
- High quality weatherised ABS cabinet with rust proof grille for outdoor usage
- Complete weather proof outdoor capable designed to meet IP55 standards
- Rear protective cover to prevent water ingress
- Available in Black colour

### **APPLICATIONS**

The iComm SMS52T is two way multipurpose monitor speaker suitable for

- Indoor applications: Restaurants, offices, museums, home theater, auditoriums, gymnasiums, F&B establishments
- Outdoor applications: Atriums, pool side, patios, backyards and more
- Contractors, custom installers & retail stores

## iComm SMS52T

Indoor / Outdoor Surface Mount Sp<u>eaker</u>







#### SPECIFICATIONS

Power Handling (AES Standard)	40W RMS / 80W Program / 160W Peak
Nominal Impedance	8 ohms
Frequency Response (-10dB)	70Hz – 20KHz
Average Sensitivity	88dB/W/m
Calculated Max SPL	104dB Continuous / 107dB Program / 110dB Peak
Low Frequency Driver	5.25" Polypropylene woofer with rubber surround
High Frequency Driver	0.5" Mylar tweeter
Input Connectors	Binding post push terminals
100V Connectivity	2W, 4W, 8W & 16W selectable via rotary switch
Cabinet	High quality, ABS with rust proof aluminum grille
Colour	Black
Wall mount bracket	Included, heavy duty swivel U bracket for horizontal and vertical mounting
Outdoor Capable	Weatherized designed to meet IP55 standards
Size (WxHxD)	160 x 260 x 155mm
Net weight	2.70Kg