



# A PREMIER GERMAN ENGINEERING MARVEL.

WWW.VALAUDIO.COM

# IMPECCABLE QUALITY AND CLARITY

# CUTTING-EDGE TECHNOLOGY AND A COMMITMENT TO PRECISION.

VAL Audio epitomises technical excellence.
Our cutting-edge solutions redefine sonic precision, delivering unparalleled audio experiences. Elevate your sound with VAL Audio's commitment to innovation and quality.

Renowned for pristine sound, our products redefine audio excellence, setting industry standards globally.



# AL audio Line

Arrays

Point Source

Integrated Commercial

Portable **Powered Systems** 

Weatherised Speakers

Subwoofers

Professional Amplifiers

Commercial Amplifiers

Smart Solutions

Microphones

Digital Signal Processor

Digital
Conference System

# LINE ARRAYS VAL AUDIO LINE ARRAY LOUDSPEAKERS OFFER HIGH

VAL AUDIO LINE ARRAY LOUDSPEAKERS OFFER HIGH EFFICIENCY, HIGH POWER HANDLING SOLUTIONS FOR THE MOST DISCERNING VENUE OR TOURING REQUIREMENT.

www.valaudio.com/line-arrays/



# WP15CXL

High performance weatherized coaxial line array loudspeaker

• Components : 1×15" LF, 1×1.4" exit coaxial HF

• Power Handling: 400W RMS

• Impedance : 8 ohm • Max SPL : 135dB





# WCX15L-500

High performance weatherized coaxial line array loudspeaker

Components: 1×15" LF, 1×1.4" exit coaxial HF

• Power Handling: 500W RMS

Impedance: 8 ohmMax SPL: 136dB



# VLA210HP

High performance Installation specific 2-way passive line array loudspeaker

Components: 2×10" LF, 1.5" exit HF
Power Handling: 800W RMS

Impedance: 8 ohmMax SPL: 135dB





# VLA210HP-ND

Ultra High performance 2-way passive line array loudspeaker

• Components : 2×10" LF, 1.5" exit HF all Neodymium drivers

• Power Handling: 900W RMS

Impedance: 8 oh
 Max SPL: 138dB







# QX8HP

High performance 2-way full range loudspeaker

Components: 1×8" LF, 1" exit HFPower Handling: 200W RMS

• Impedance : 8 ohm • Max SPL : 125dB





# QX10HP

High performance 2-way full range loudspeaker

Components: 1×10" LF, 1" exit HI
Power Handling: 300W RMS

Impedance : 8 ohmMax SPL : 127dB





# QX12HP

High performance 2-way full range loudspeaker

Components: 1×12" LF, 1" exit HF
Power Handling: 400W RMS

Impedance: 8 ohmMax SPL: 130dB





# QX15HP

High performance 2-way full range loudspeaker

Components: 1×15" LF, 1" exit HF
Power Handling: 600W RMS

• Impedance : 8 ohm





# ZX15HP

Ultra High performance 2-way full range loudspeaker

• Components: 1×15" LF, 1.4" exit HF

• Power Handling: 800W RMS

• Impedance: 8 ohm

• Max SPL: 134dB





## WP8CXT

High performance weatherized coaxial loudspeaker

• Power Handling: 150W RMS

• Max SPL : 124dB





# WCX8T-200

High performance weatherized coaxial loudspeaker

• Components : 1×8" LF, 1×1" exit coaxial HF

• Power Handling : 200W RMS

• Impedance : 8 ohm / 100V LMT in-built

• Max SPL: 124.5dB





# INTEGRATED COMMERCIAL

VAL AUDIO ICOMM SERIES SHORT FOR INTEGRATED COMMERCIAL IS AIMED AT THE FIXED INSTALLATION MARKET.

www.valaudio.com/integrated-commercial-icomm-series/



# **ICOMM CS4.2T**

Two way full range coaxial ceiling speaker

- Components: 1×4" LF, 0.5" dome tweeter
- Power Handling: 25W RMS / 100W peak
- 100V operation only
- LMT in-built





# **ICOMM CS5.2T**

Two way full range coaxial ceiling speaker

- Components : 1×5.25" LF, 0.75" dome tweeter
- Power Handling: 30W RMS / 120W peak
- 8 ohm / 100V operation possible
- I MT in-huilt





# **ICOMM CS6.2**

High end two way full range coaxial ceiling speaker

- Components : 1×6.5" LF, 1" silk dome tweeter
- Power Handling: 50W RMS / 200W peak
- Impedance : 8 ohm
- LMT version available





# **ICOMM PA6T**

Slim profile full range wall mount PA speaker

- Components : 6" full range driver
- Power Handling: 15W RMS / 60W peak
- 100V operation only, LMT In-built
- High quality ABS cabinet





# **ICOMM SMS52T**



Two way full range indoor / outdoor surface mount speaker

- Components : 1×5.25" LF, 0.5" tweeter • Power Handling : 40W RMS / 160W peak
- 8 ohm / 100V operation possible, LMT in-built
- Swivel mounting bracket included



# **ICOMM SMS62T**



Two way full range indoor / outdoor surface mount speaker

- Components: 1×6.5" LF, 1" tweeter
- Power Handling: 60W RMS / 240W peak
- 8 ohm / 100V operation possible, LMT in-built
- Swivel mounting bracket included



# **ICOMM SMS82T**



Two way full range indoor / outdoor surface mount speaker

- Components : 1×8" LF, 1" tweeter
- Power Handling: 100W RMS / 400W peak
- 8 ohm / 100V operation possible, LMT in-built
- Swivel mounting bracket included



# ICOMM WM52T-BLK



High performance 2-way indoor / outdoor full range speaker

- Components: 1×5" LF + passive radiator, 1" silk dome tweeter
- Power Handling: 50W RMS / 200W peak
- 8 ohm / 100V operation possible, LMT in-built
- Swivel mounting bracket included



# ICOMM WM52T-WH



High performance 2-way indoor / outdoor full range speaker

- $\bullet$  Components : 1×5" LF + passive radiator, 1" silk dome tweeter
- Power Handling: 50W RMS / 200W peak
- 8 ohm / 100V operation possible, LMT in-built
- Swivel mounting bracket included





# **ICOMM PS52T**

High performance 2-way indoor / outdoor full range pendant speaker

- Components : 1×5" LF, 1" silk dome tweeter
- Power Handling: 50W RMS / 200W peak
- 8 ohm / 100V operation possible, LMT in-built
- Mounting hardware included





# **ICOMM WM42T**

High performance 2-way indoor / outdoor full range speaker

- Components :  $1\times4''$  LF,  $1\times0.8''$  tweeter
- Power Handling: 40W RMS / 160W peak
- 16 ohm / 100V operation possible, LMT in-built
- Easy mounting ball and Swivel mounting





# ICOMM WM62T

High performance 2-way indoor / outdoor full range speaker

- Components :  $1\times6"$  LF,  $1\times1"$  compression driver
- Power Handling: 80W RMS / 320W peak
- 16 ohm / 100V operation possible, LMT in-built
- Swivel mounting bracket included





# **ICOMM PSW200**

High performance active subwoofer

- Components · 1×12" LF
- Power Handling: 200W RMS / 800W peak
- Active, amplifier in-built
- Down firing woofer



# INTEGRATED COMMERCIAL

VAL audio iComm series short for Integrated Commercial is aimed at the fixed Installation market. High-quality, high-performance products, weatherised models with high quality ABS cabinets, Internal LMT for 70V/100V easy operation, mounting brackets included for easy installation and only premium components used.

# PORTABL POWERE

VAL AUDIO X-LINE12 & X12A OFFERS AN ALL IN ONE POWERED. PORTABLE SOLUTION.

www.valaudio.com/portable-column-array-2/



# X-LINE12

Portable powered column array speaker

- 1×12" subwoofer 1000W RMS power output



# **X12A**

Portable powered PA speaker

- Components: 1×12" high-excursion woofer, 1×1.75" dome compression driver
- 700W RMS power output
- Class leading 130dB max SPL
- Integrated DSP, mixer with Bluetooth(TWS), Mic/Line input

### PORTABLE POWERED SYSTEM

VAL Audio powered systems provide an all-in-one, portable solution for all your PA needs. Featuring advanced DSP for precise sound control, a high-efficiency Class D amplifier, and versatile input options, including Bluetooth (TWS), these systems ensure seamless operation and powerful performance. Built with lightweight yet durable enclosures, they combine portability with reliability. Renowned for exceptional sound quality and trusted VAL Audio engineering, these systems are perfect for both fixed installations and portable PA applications.





# WP8CXT

High performance weatherized coaxial loudspeaker

- Components: 1×8" LF, 1×1" exit coaxial HF
- Power Handling: 150W RMS
- Impedance : 8 ohm / 100V LMT in-built
- Max SPL: 124dB



# WCX8T-200

High performance weatherized coaxial loudspeaker

- Components: 1×8" LF. 1×1" exit coaxial HF
- Power Handling: 200W RMS
- Impedance: 8 ohm / 100V LMT in-buil
- Max SPL: 124.5dB



# WP15CXL

High performance weatherized coaxial line array loudspeaker

- Components: 1×15" LF, 1×1.4" exit coaxial HF
- Power Handling: 400W RMS
- Impedance : 8 ohm
- Max SPL : 135dB



# WCX15L-500

High performance weatherized coaxial line array loudspeaker

- Components: 1×15" LF, 1×1.4" exit coaxial HF
- Power Handling: 500W RMS
- · Impedance : 8 ohn · Max SPL · 134dB







# **WP312**



## Weatherised 3-way line array loudspeaker

• Components : 2x12" LF, 2 x 1.4" exit coaxial HF+MF neodymium driver

• Power Handling: 800W RMS LF, 300W RMS MF+HF

Impedance: 8 ohm LF, 16 ohm MF+HF
Max SPL: LF 136dB, MF+HF 140dB



# SUBWOOFERS

VAL AUDIO FEATURE HIGH PERFORMANCE HIGH OUTPUT SUBWOOFERS DESIGNED TO MEET ANY AND ALL LOW FREQUENCY REINFORCEMENT APPLICATIONS FROM HOME THEATRES, AUDITORIUMS, BARS & CLUBS AND TOURING APPLICATIONS.

www.valaudio.com/subwoofers/



# **ICOMM PSW200**



High performance active subwoofer

• Components : 1×12" LF

• Power Handling: 200W RMS / 800W peak

• Active, amplifier in-built

Down firing woofer



# SW118HP

High performance vented subwoofer

Components: 1×18" LF
Handling: 1000W RMS
Impedance: 4 ohm
Max SPL: 135dB





# SW218UHP

Ultra high performance direct radiating subwoofer

• Components : 2×18" LF

• Power Handling: 2800W RMS

• Impedance : 4 ohm

• Max SPL: 141dB





# PROFESSIONAL AMPLIFIERS

VAL AUDIO OFFERS CLASS LEADING AMPLIFICATION FOR POWERING OUR SPEAKERS OFFERING MODERN CLASS H AND CLASS D SOLUTIONS.

www.valaudio.com/professional-amplifiers/



## **V40**

### **Professional Power Amplifier**

- 4 channel 4x600W at 4 ohms.
- Class D
- 1U frame size
- Ultra Lightweight only 5.9 Kg



# X4.12

### **Professional Power Amplifier**

- 4 channel amplifier
- 4x800W at 8 ohms, 4x1250W at 4 ohms
- Class H with toroidal transformer PSU
- 2U frame size



# X2.15

#### **Professional Power Amplifier**

- 2 channel amplifier
- 2×1000W at 8 ohms 2×1500W at 4 ohm
- Class H with toroidal transformer PSU
- 2U frame size



# X2.35

### **Professional Power Amplifier**

- 2 channel amplifier
- 2x2000W at 8 ohms, 2x3500W at 4 ohms
- Class D with toroidal transformer PSU
- 2U frame size





# **MA120**

#### Mixer amplifier

- Max power output 120W
- 3 aux and 2 mic inputs
- 4-16 ohm, 70V/100V output
- Bluetooth / USB / FM receiver with LCD display



# **MA360**

#### Mixer amplifier

- Max power output 360W, 6 zone output available
- 2 aux and 3 mic inputs
- 4-16 ohm, 70V/100V output
- USB / FM / Bluetooth media player



# **MA480**

#### Mixer amplifier

- Max power output 480W
- 3 aux and 2 mic inputs
- 4-16 ohm, 70V/100V output
- USB / FM / Bluetooth media player



### **ZA4100**

#### 4 Stereo zone amplifier

- 100W per channel, 4 stereo zone amplifier
- Individual volume control on each zone
- 2 RCA + 1 Mic inpu
- Bluetooth / USB / SD card/ EM receive







# SMART SOLUTIONS

VAL AUDIO COMBINE INNOVATION AND ADVANCED TECHNOLOGY TO CREATE INTELLIGENT AUDIO SOLUTIONS TAILORED FOR MODERN APPLICATIONS.

www.valaudio.com/smart-solutions/





Intelligent Automixer



- Intelligent feedback suppression
- LCD display
- Easy front panel operation





# **VP800**

**Smart Power Management System** 

- MCU-Controlled Precision
- Eight Channels of Adjustable Power
- Front-Mounted Open Power Sockets
- Flexible Voltage Protection



### **SMART SOLUTIONS**

VAL Audio's Smart Products combine innovation and advanced technology to create intelligent audio solutions tailored for modern applications.

With VAL Audio's Smart Products, experience smarter, more efficient audio solutions for today's dynamic needs.





# VM5v

Wired dynamic professional microphone

- Cardioid polar pattern
- Silent on/off switch
- Rugged zinc die-cast body
- XLR-M connector





# VM5i

Wired dynamic professional microphone

- Cardioid polar pattern
- Silent on/off switch
- Rugged zinc die-cast body
- XLR-M connector





# VGN16SC

Wired podium gooseneck microphone

- Condenser element
- Supercardiod polar pattern
- 16" gooseneck length
- Rugged metal base with on/off switch







# PR04500-HD



- Two wireless handheld microphone set
- Ouick setup via sync and IR
- 200 selectable frequencies per receiver
- True diversity 1U 19" rack mount receiver





# PRO4500-LD

High performance Digital wireless microphone system

- Two bodypack lavalier wireless microphone set
- Quick setup via sync and IR
- 200 selectable frequencies per receiver
- True diversity 1U 19" rack mount receiver





# PRO4500-COMBO





- Quick setup via sync and IR
- 200 selectable frequencies per receiver
- True diversity 1U 19" rack mount receiver



## PR01000

High Performance UHF Digital Wireless **Dual Handheld Microphone System** 

- Cutting-edge two wireless handheld microphone set
- Advanced PLL technology and ID lock system
- Pair transmitter and receiver using scan and IR sync feature
- True diversity 1U 19" rack mount receiver (200 selectable frequencies)



### **MICROPHONES**

VAL audio range of professional microphones feature a wide range of microphones designed to suit the most discerning application and user. Our range consists of wired mics, gooseneck podium mics and a range of Digital cordless mics. All microphones are designed and manufactured with the highest standards to meet your miking needs and complement VAL audio systems.







# DIGITAL SIGNAL PROCESSOR

VAL AUDIO OFFERS A RANGE OF DSP SOLUTIONS RANGING FROM LOUDSPEAKER MANAGEMENT SOLUTIONS TO MATRIX DSP SOLUTIONS

www.valaudio.com/digital-signal-processor/



**SP48** 

# High Performance Loudspeaker management system

- 4 input 8 output DSP
- 32/40 bit floating point DSP with 96KHz sampling rate
- Parametric EQ / Low-shelf / Hi-shelf / ALL PASS filters
- Front panel USB for easy PC connectivity



DSP48

# High performance loudspeaker management system

- 4 input 8 output DSP
- SHARC 400MHz 32/40 bit floating point DSP
- 96KHz sampling rate, ELNA capacitors
- PEQ / Low-shelf / Hi-shelf / ALL PASS filters



## DSP88

## High performance digital signal processor

- 8 input 8 output DSP
- 400 Mhz 24 bit floating point DSP processor
- 48 KHz sampling rate
- 2 USB, ethernet and RS232/RS485 contro





### High performance digital signal processor

- 16 input 16 output DSP
- 400 Mhz 32/40 bit floating point DSP processor
- 48 KHz sampling rate
- Ethernet, USB, RS232, RS485, GPIO port control







# DSP4410-D



#### Dante Network Audio Interface Device

- Strictly adhering to industry-leading Dante network audio standard
- Four analog Mic/Line inputs and four analog line outputs
- Seamlessly integrates into any existing Dante network
- High-performance ADC PCM4204







# **VCS1000D**



- AUDIO-LINK Digital ring network technology achieving fully Digital signal transmission and processing
- High quality audio with 48KHz sampling rate
- Sleek and compact chairman & delegate unit can be used table top or flush mount
- Advanced noise cancellation technology and USB recording







# CONTACT



contact@valaudio.com



Instagram



**Facebook**