X4.12 Professional Power Amplifier





When it comes to selecting an amplifier that delivers outstanding power, exceptional warmth, and unparalleled versatility, the VAL Audio X Series is your ultimate solution. Engineered for both touring and fixed installations, the X4.12 exemplifies the legendary performance and reliability of the X Series, now re imagined in a sleek and modern 2U chassis.

The X4.12 is a powerhouse four-channel Class H amplifier, featuring a robust, high-current Toroidal power supply. With an impressive output of 4 x 800W at 8Ω and 4 x 1250W at 4Ω , this amplifier is designed to meet the demands of even the most rigorous applications. Its flexible configuration allows it to operate as a 4/3/2-channel amplifier, adapting effortlessly to your specific needs.

Equipped with an advanced cooling system powered by four high-speed, temperature-controlled fans, the X4.12 ensures optimal performance while maintaining cool operation under any conditions. For seamless connectivity, the amplifier includes high-quality XLR inputs with a link feature, along with speakon and binding post outputs for maximum flexibility.

When you require a no-compromise amplifier capable of running continuously while delivering class-leading performance and sound quality, look no further than the VAL Audio X Series - where innovation meets reliability.

KEY FEATURES

- Unique 4ch Power amplifier in a modern 2U compact design
- For both Touring and Fixed Installations
- Immesse flexibility usable as a 4/3/2ch power amplifier
- Highly efficient Class H Technology
- Warm and Sweet sounding amplifier
- Robust and strong Toroidal PSU
- High damping factor ≥800
- Selectable input sensitivity -0.775V/1.0V/1.44V
- Advanced cooling system with high speed temperature controlled fans
- XLR inputs with link connectors
- Professional XLR inputs with link connectors, speakon & binding post output connectors

X4.12 Professional Power Amplifier





APPLICATIONS

- Live Performance & Touring: Provides powerful, reliable sound for concerts, stage performances and events.
- House of Worship: Delivers clear and consistent audio for sermons, music and large congregations.
- Theaters & Auditoriums: Ensures high-fidelity sound for dramatic performances, presentations and speeches.
- Nightclubs & Entertainment Venues: Offers robust audio output for vibrant, dynamic soundscapes.
- Corporate Events & Conferencing: Facilitates high-quality audio for presentations, meetings and conferences.
- **Fixed Installations:** Ideal for schools, lecture halls, stadiums and other permanent setups requiring professional grade audio amplification.

SPECIFICATION

MODEL	X4.12
Power (*EIA Standard)	
8Ω Output	4 x 800W
4Ω Output	4 x 1250W
2Ω Output	4 x 1600W
Bridged 8Ω Output	2 x 2500W
Output Circuit	Class H
Frequency Response (±1dB)	10Hz - 30kHz
Input Sensitivity	0.775V / 1.0V / 1.44V
Input Impedance	Balanced $20 \text{K}\Omega$ Unbalanced $10 \text{K}\Omega$
Crosstalk (rated power 8Ω 1kHz)	≥65dB
Signal to Noise Ratio	≥101dB
Damping Factor	≥800
Total Harmonic Distortion (8 Ω 1/10 Po)	<0.1%
Rack space	2U
Cooling System	4 nos temperature controlled high speed fans
Protection	Comprehensive protection circuitry - Soft-Start, Short-Circuit, Over and Under-Voltage, Over-Current, Over-Load, DC Output, Temperature
Net Weight (Kg)	26.75
Size (mm)	483 x 490 x 98